

S.N.	SIZE	WIRE DIA	WEIGHT (4x100)	APERTURE IN MICRONS	OPENING AREA %
1	16x24	0.55	87.3	1038	43
2	16x25	0.50	72.2	1088	47
3	16x26	0.45	57.9	1138	51
4	16x27	0.40	45.7	1188	56
5	16x28	0.35	34.6	1238	61
6	18x25	0.50	81.2	911	42
7	18x26	0.45	65.1	961	46
8	18x27	0.40	51.4	1011	51
9	18x28	0.35	39.0	1061	57
10	20x25	0.50	89.1	770	37
11	20x26	0.45	71.4	820	42
12	20x27	0.40	56.4	870	47
13	20x28	0.35	43.3	920	52
14	20x30	0.30	31.8	970	58
15	22x32	0.26	26.3	895	60
16	24x28	0.35	51.4	708	45
17	24x29	0.34	48.5	718	47
18	24x30	0.30	37.8	758	52
19	30x30	0.30	46.9	547	42
20	30x31	0.29	44.2	557	44
21	30x32	0.26	35.5	587	48
22	36x34	0.22	30.4	486	48
23	40x32T	0.27	51.3	365	34
24	40x32	0.26	46.6	375	36
25	40X32T	0.26	47.6	375	36
26	40x32	0.25	43.3	385	38
27	40X32T	0.25	44.3	385	38
28	40x34	0.22	33.8	415	43
29	40X34T	0.22	34.5	415	43
30	40x36	0.19	25.2	445	50
31	40X36T	0.19	25.7	445	50
32	40x36	0.18	22.8	455	52
33	40X36T	0.18	23.2	455	52
34	40x38	0.15	15.8	485	59
35	40X38T	0.15	16.1	485	59
36	50x36	0.19	31.6	318	40
37	50x36	0.18	28.5	328	42
38	50x38	0.15	19.8	358	50
39	60X34T	0.22	51.3	203	24
40	60x36	0.19	37.6	233	31
41	60x36 T	0.19	38.4	233	31
42	60x36	0.18	33.9	243	34
43	60x38	0.15	23.6	273	42
44	60x38 T	0.15	24.1	273	42
45	80x38T	0.15	31.8	168	29
46	80x39	0.13	23.4	188	36
47	80x40	0.12	20.0	198	39
48	100x41	0.11	21.0	144	33
49	100x42	0.10	17.4	154	38
50	24x110	0.35X0.25	86.7	60.7+26	0
51	24x110	0.37X0.27	99.9	70.7+29.2	0